



Specifications Ledvance LED Panel  
IndiviLED 33W 4000lm - 840 Cool  
White | 60x60cm - UGR <16 - Dali  
Dimmable

[View Product](#)

## General Information

|                      |                                 |
|----------------------|---------------------------------|
| SKU                  | 243689                          |
| EAN                  | 4058075503861                   |
| Manufacturer Code    | 4058075503861                   |
| Brand                | Ledvance                        |
| Manufacturer Name    | PL INDV 600 33W/4000K DALI LEDV |
| Budgetlight warranty | 5 Years                         |
| Average Lifetime (h) | 60000                           |
| Product Serie        | IndiviLED                       |

## Technical Information

|                             |                    |
|-----------------------------|--------------------|
| Technology                  | LED Integrated     |
| Replaces (Watt)             | 4x18               |
| Wattage                     | 33W                |
| Voltage (V)                 | 220-240            |
| Dimmable                    | Dimmable with Dali |
| Colour Code                 | 840 Cool White     |
| Colour temperature (Kelvin) | 4000 Cool White    |
| Colour Rendering (Ra)       | 80-89              |
| Colour of Light             | White              |
| Light colour options        | Single Color       |

|                        |                        |
|------------------------|------------------------|
| Including bulb         | Yes                    |
| Luminous Flux (Lumen)  | 4000lm                 |
| Lumen per watt         | 121                    |
| IP-rating              | IP40                   |
| Impact Protection (IK) | IK08 - 5 joules        |
| Fixture Connection     | Screw terminal, 2-pole |
| Power factor           | >0.90                  |
| Product Type Category  | LED Panel              |

## Fixture Information

|                       |                                |
|-----------------------|--------------------------------|
| Mounting Method       | Recessed                       |
| Unified Glare Rating  | < 16 - for offices and schools |
| Optical Cover         | PC (Polycarbonate)             |
| Operating Temperature | -20 to +45                     |
| Emergency Lighting    | No Emergency Unit              |
| Colour of the Fixture | White                          |
| Housing               | Aluminium                      |
| Colour of material    | White                          |

## Dimensions

|                |         |
|----------------|---------|
| LED panel size | 60x60cm |
| Length (mm)    | 595     |
| Width (mm)     | 595     |
| Height (mm)    | 50      |

## Why Budgetlight?



Guaranteed **budget prices**



Up to **7 years warranty**

## Sensor Information



**Easy** return process



Long-life **LED solutions**

|                |           |
|----------------|-----------|
| Type of sensor | No Sensor |
|----------------|-----------|