



**Specifications Ledvance LED  
Downlight Comfort Opal White  
18W/15W/12W  
2160lm/1800lm/1440lm 95D - 930-940  
CCT | Cutout 150mm - IP44 - Best  
Colour Rendering**

[View Product](#)

## General Information

|                      |                                      |
|----------------------|--------------------------------------|
| SKU                  | 254956                               |
| EAN                  | 4099854490941                        |
| Manufacturer Code    | 4099854490941                        |
| Brand                | Ledvance                             |
| Manufacturer Name    | DL CMFT D150 P 18W MS 940 OP WT LEDV |
| Budgetlight warranty | 5 Years                              |
| Average Lifetime (h) | 100000                               |

## Technical Information

|                             |                                  |
|-----------------------------|----------------------------------|
| Emergency Lighting          | No Emergency Unit                |
| Tiltable                    | No                               |
| Technology                  | LED Integrated                   |
| Replaces (Watt)             | 2x18                             |
| Wattage                     | 18W                              |
| Voltage (V)                 | 220-240                          |
| Dimmable                    | Not Dimmable                     |
| Colour Code                 | 930 Warm White, 940 Cool White   |
| Colour temperature (Kelvin) | 3000 Warm White, 4000 Cool White |
| Colour Rendering (Ra)       | 90-99                            |

|                       |                          |
|-----------------------|--------------------------|
| Colour of Light       | White                    |
| Light colour options  | CCT                      |
| Beam Angle (degree)   | 95                       |
| Luminous Flux (Lumen) | 2160lm                   |
| Lumen per watt        | 120                      |
| Power factor          | >0.90                    |
| Unified Glare Rating  | < 23 - for general areas |
| Optical Cover         | Opal                     |
| Product Type Category | LED Downlight            |

## Fixture Information

|                        |                        |
|------------------------|------------------------|
| Mounting Method        | Recessed               |
| Cut out (mm)           | 150                    |
| IP-rating              | IP44                   |
| Impact Protection (IK) | IK03 - 0.35 joule      |
| Operating Temperature  | -20 to +40             |
| Housing                | Aluminium              |
| Colour of the Fixture  | White                  |
| Fixture Connection     | PI [Push-in connector] |

## Dimensions

|               |     |
|---------------|-----|
| Height (mm)   | 57  |
| Diameter (mm) | 160 |

**Sensor Information**  Guaranteed **budget prices**  Up to **7 years warranty**

Type of sensor

 **Easy** return process

No Sensor



Long-life **LED solutions**